

BLANK PAGE



Indian Standard

SPECIFICATION FOR ANTHRAQUINONE, TECHNICAL

UDC 668.812



© Copyright 1972

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 1

AMENDMENT NO. 1 JUNE 1973

TO

IS: 6259-1971 SPECIFICATION FOR ANTHRAQUINONE, TECHNICAL

Corrigendum

(Page 7, clause A-2.2.1, line 3) — Substitute '100 percent' for '10 percent',

(CDC 46) V

Indian Standard

SPECIFICATION FOR ANTHRAQUINONE, TECHNICAL

Dye Intermediates Sectional Committee, CDC 46

Chairman

Shri Jogander Singh

Members

Sикі В. М. Вканмі

SHRUG A KULKARNI SHRIS V. DESM (Alternate)

SHRIS, M. MIRIA

SHRI M. V DISAI (Alternate)

Dr R. B. Milka

Shri B. M. Palit

Suri Y. R. Minix (Alternate)

SHRI RATI NDRA SHANKAR

SHRI M S. FAWAKIEY (Alternate)

DRR. J RAIHI

SHRIK L. RAINI (Alternate)

SHRI SANJOKH SINGH

SHRIKTIWANI SINGH (Alternate)

DR H. A. SHAH

SHRIN. K SIN | Alternate)

SHRI S. J. SHAR

SHRI M. B. MIHIA (Alternate)

Dr D. R. Shridhar

DR R. N. DHAR (Alternate)

Dr P. V. Sebramaniam

DR N. V. SHAH (Alternate)

DR D. R. SWAYAMPATI

DR O. P. MITTAL (Alternate)

SURI MUKUND FURAKHIA

SHRI ANIL MEHRA (Alternate)

DR H. P. VANDREWALA

DR P. N. PANDII (Alternate)

Supt D. Das Gurla,

Ducctor (Chem.)

Representing

Directorate General of Technical Development,

New Della

Atic Industries I td, Bulsar

Amar Dyc-Chem Ltd, Bomb iv

Atul Products Ltd, Bulsar

Nitional Chemical Laboratory (CSIR), Poona

ICI (India) Private Ltd, Calcutta

Indian Dyestuff Industries I td, Bombay

Sudarshan Chemical Industries Pvt Ltd, Poona

National Chemical Industries, New Delhi

Development Commissioner, Small Scale Industries,

New Delhi

Indian Chemical Manufacturers Association,

Calcutta

Indian Drug: & Pharmaceuticals Ltd, New Delhi

Colour-Chem Ltd, Bombay

Suhrid Geigy Ltd, Baroda

The Dvestuffs Manufacturers Association of India,

Bombay

Chemicals Ltd, Rasayani Hindustan Organic

(Maharashtra)

Director General, ISI (Ex-officio Member)

Secretary

SHRI M. A. U. KHAN Assistant Director (Chem.), ISI

(Continued on page 2)

INDIAN STANDARDS INSTITUTION

MANAK BHAVAN, 9 BAHADUR SHAH ZALAR MARG NLW DELIII I

IS: 6259 - 1971

(Continued from page 1)

Panel for Anthraquinones, CDC 46: P 7

Representing

Convener

SHRI RAJENDRA SHANKAR Indian Dyestuff Industries Ltd, Bombay

Members

SRRI M. S. TAWAKLEY (Alternate to Shri Rajendra Shankar) SHRI B. M. BRAHME Ati


Atic Industries Ltd, Bulsar

Indian Standard

SPECIFICATION FOR ANTHRAQUINONE, TECHNICAL

O. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 23 August 1971, after the draft finalized by the Dye Intermediates Sectional Committee had been approved by the Chemical Division Council.
- 0.2 Anthraquinone (C₁₄H₈O₂) is a very important dye intermediate used extensively in the manufacture of vat dyes, disperse dyes and wool dyes. It finds application in textile printing industry, some pharmaceutical preparations and also as pesticide, It is represented by the following structural formula:



(Molecular weight=208)

- 0.3 Anthraquinone is a flammable substance and constitutes a slight fire hazard. The flash point is 185°C. Anthraquinone dust is readily flammable and suitable precautions should be taken. Prolonged exposure to anthraquinone dust may cause allergic symptoms.
- 0.4 This standard is one of a series of Indian Standards on dye intermediates. A complete list of such standards is given on page 8.
- 0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with

IS: 6259 - 1971

IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements and the methods of sampling and test for anthraquinone, technical.

2. REQUIREMENTS

- 2.1 Description The material shall be in the form of a pale yellow to beige coloured light crystalline powder and shall be free from visible impurities.
- 2.2 The material shall also comply with the requirements given in Table 1.

TABLE 1 REQUIREMENTS FOR ANTHRAQUINONE, TECHNICAL

St. No.	CHARACTERISTIC	REQUIREMENT	METHOD OF TEST (REF TO CL No. IN)		(Ref to C	Cr No. in)
			Appendix A	IS: 5299-1969*		
(1)	(2)	(3)	(4)	(5)		
i)	Moisture content, percent by weight, Max	0-2		9.1 or 9.3		
ii)	Sulphated ash, percent by weight, Max	0.5		11.2		
iii)	Melting point, °C	Shall melt within the range of 3°C including 282°C	-	8		
iv)	Anthraquinone content, percent by weight, Min	98.0	A-2	Service		

^{*}Methods of sampling and tests for dye intermediates.

3. PACKING AND MARKING

- 3.1 Packing The material shall be suitably packed in polythene bags or paper bags or as agreed to between the purchaser and the supplier.
- 3.2 Marking Each container shall be securely closed and shall bear legibly and indelibly the following information:
 - a) Name of the material;
 - b) Name of the manufacturer;
 - c) Lot or batch number;
 - d) Tare, net and gross weights; and
 - e) Recognized trade-mark; if any.

**

^{*}Rules for rounding off numerical values (revised).

ſ,

3.2.1 The containers may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act, and the Rules and Regulations made thereunder. Presence of this mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard, under a well-defined system of inspection, testing and quality control during production. This system, which is devised and supervised by ISI and operated by the producer, has the further safeguard that the products as actually marketed are continuously checked by ISI for conformity to the standard. Details of conditions, under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

4. SAMPLING

- 4.1 Preparation of Test Samples—The material shall be sampled according to the procedure given in 3 of IS: 5299-1969*.
- 4.2 Number of Tests Tests for the determination of all the characteristics specified in this standard shall be conducted on the composite sample.
- 4.3 Criteria for Confermity For declaring the conformity of the lot to this standard, test results for each of the characteristics shall satisfy the relevant requirement specified.

APPENDIX A

[Table 1, Item (iv)]

METHODS OF TEST FOR ANTHRAQUINONE, TECHNICAL

A-1. QUALITY OF REAGENTS

A-1.1 Unless specified otherwise, pure chemicals and distilled water (see IS: 1070-1960†) shall be employed in tests.

Note - 'Pure chemicals' shall mean chemicals that do not contain impurities which affect the results of analysis.

A-2. DETERMINATION OF ANTHRAQUINONE CONTENT

A-2.0 General — The following two methods have been prescribed for the determination of anthraquinone content. The first method (Method A) is the referee method which shall be used in case of any dispute, whereas the second method (Method B) is for the routine analysis.

^{*}Methods of sampling and tests for dye intermediates. †Specification for water, distilled quality (revised).

A-2.1 Method A

- A-2.1.1 Principle In this method the anthraquinone is reduced to its leuco derivative by heating to 60 to 80°C with an aqueous solution of caustic soda and sodium hydrosulphite. The sodium salt of leuco anthraquinone forms a bright red coloured solution and is filtered through a sintered glass funnel. The leuco anthraquinone is oxidized back to anthraquinone by the addition of hydrogen peroxide or by aeration. The precipitated anthraquinone is filtered through a sintered glass crucible washed free of alkali, dried and weighed.
- A-2.1.2 Procedure Prepare a solution of 10 g of sodium hydrosulphite (see IS: 1919-1961*) in 100 ml of 10 percent sodium hydroxide. Allow to stand for one hour and filter through a filter paper.
- A-2.1.2.1 Weigh accurately about 1 g of the powdered anthraquinone and transfer it into a 250-ml conical flask. Add 100 ml of water and 50 ml of the hydrosulphite solution prepared as above. Heat the mixture for 10 minutes in a water-bath at 60 to 80°C. There results a bright red coloured solution of leuco anthraquinone. Filter through a G2 sintered glass crucible; taking care not to allow oxidation of the material on the crucible or foaming of the filtrate (do not apply too high a suction for filtration). Before starting filtration, put a little diluted (10 times) hydrosulphite solution on the filter. See that the crucible is never empty. Treat the undissolved anthraquinone remaining in the flask with dilute (10 times) hydrosulphite solution at 60 to 80°C. Reduction is complete when the filtrate is free of any tinge of red.
- A-2.1.2.2 To the filtrate at 60 to 80°C, add 10 ml of 30 percent hydrogen peroxide to oxidize back the anthraquinone. Oxidation is complete when there is no red colour. Oxidation may also be carried out by passing a slow current of air through the leuco solution at 60 to 80°C (considerable foaming occurs in aeration). The precipitate is filtered through a tared G4 sintered glass crucible, washed free of alkali with hot water and dried at 100 to 110°C to constant weight.

A-2.1.3 Calculation

Assay, percent by weight =
$$\frac{W_s}{W_1} \times 100$$

where

 W_0 = weight in grams of the regenerated anthraquinone, and W_1 = weight in grams of sample taken for the test.

^{*}Specification for sodium hydrosulphite, technical.

A-2.2 Method B

- A-2.2.1 Principle This method makes use of the great stability of anthraquinone to the action of sulphuric acid. Anthraquinone is dissolved in 10 percent sulphuric acid and held at 95 to 100°C for 10 to 15 minutes. The impurities in anthraquinone are digested by this process. Anthraquinone is reprecipitated by allowing the solution to absorb water gradually over 12 hours. It is then filtered, washed free of acid and dried.
- A-2.2.2 Procedure Weigh accurately about 1 g of anthraquinone and place it in a porcelain dish of 20 cm diameter. Carefully pour 10 ml of 100 percent sulphuric acid in order to cover all anthraquinone crystals. Put the dish on a water-bath at 95 to 100°C. Maintain for 10 to 15 minutes. Remove from water-bath, keep in a bell jar containing water. Allow to absorb moisture over 12 hours. Drown the contents of the dish into 200 ml water contained in a 400-ml beaker, washing down the dish well. Filter through a tared G4 sintered glass crucible and wash with distilled water till the filtrate is neutral. Then, wash with 200 ml of boiling potassium hydroxide solution (0·1 g dissolved in 100 ml) and finally with boiling distilled water till free of alkalinity. Dry at 100 to 110°C to constant weight.

A-2.2.3 Calculation

Assay, percent by weight
$$=\frac{W_2}{W_1} \times 100$$

where

 W_2 = weight in grams of reprecipitated anthraquinone, and W_1 = weight in grams of sample taken for test.

INDIAN STANDARDS

ON

Dye Intermediates

IS:						Rs
2630-1964	Nitrobenzene, technical	***	•••	•••	•••	3.00
2740-1964	Sulphanilic acid, technical	•••	•••	•••	• • • •	3.00
2741-1964	β-naphthol	•••	•••	•••	•••	3· 50
2744-1964	α-naphthylamine	•••	•••	•••	•••	3.00
2833-1964	Aniline, technical	•••	•••	***	•••	4.50
3229-1965	Naphthionic acid (sodium salt)	•••	•••	•••	•••	2 ·50
3242-1965	β-oxy naphthoic acid (bon acid)	•••	•••	•••	•••	3.00
3562-1965	p-nitrotoluene, technical	•••	•••	•••	•••	4.50
4265-1967	4-4' Diaminostilbene 2-2' disulphor	nic ac ıd	***	***	•••	4.00
4334-1967	o-chloroaniline	•••	•••	•••		5.00
4335-1967	m-chloroaniline	•••	***	***	•••	5.00
4336-1967	p-chloroaniline	•••	•••	••	•••	5.50
4425-1967	p-Nitrotoluene o-sulphonic acid	***	***	***	•••	4.00
4523-1968	Acctoacetanilide	•••	•••	•••	•••	4.00
4524-1968	Acetoacet-o-chloroanilide	•••	***	•••	•••	4.00
4525-1968	p-Aminoacetanilide	•••	***	•••	•••	4.00
4526-1968	2, 5 Dichloroaniline	•••	***	***	•••	5.00
4527-1968	2-Nitto-4-chlorotoluene	•••	•••	•••	•••	5.00
4528-1968	4-4'-Dinitrostilbenc-2-2'-disulphoni	c acid (dise	odium salt)	•••		5.00
5042-1969	1-Aminoanthraquinone	•••	***	•••	•••	4.00
5043-1969	2-Aminoanthraquinone	***	•••	•••	•••	4.00
5 044-19 69	Benzanthrone	•••	•••	•••	•••	5 ·00
5045- 1969	Metanilic acid, technical	•••	***	•••	•••	4.00
5299-1969	Methods of sampling and tests for o	lye interme	diates	***	•••	12.00
5438-1969	Nitrobenzene-m-sulphonic acid (soc	dium salt)	***	***	•••	3.50
6258-1971	o-Nitroanisole	***	***	•••	•••	2.00
6259-1971	Anthraquinone, technical	•••	•••	•••	•••	2 ·50
6260-1971	p-Nitroanisole	•••	***	•••	•••	2 ·00
6264-1971	J-Acid	***	•••	•••	•••	2.00
6265-1971	Quinizarine, technical	•••	•••	•••	•••	2·5 0
6266-1971	1:4 Diaminoanthraquinone, technic	al	•••	•••		3· 50

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION INDIAN STANDARDS

Over 6 500 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Chemical Group fall under the following categories:

Acids Adhesives	Linters and allied products Lubricants and related products
Alcohols and allied products	Oil pastes
Alkalis	Oils & fats, oleaginous seeds and
Brushware	fruits
Ceramicware, enamelware and labora- tory porcelain	Painters' materials (miscellaneous) Paper and its products
Chemical hazards and safety	Paper and pulp board packaging
Chemicals, inorganic (miscellaneous)	materials
Chemicals, organic (miscellaneous)	Portumery materials, natural and
Coal and coke	synthetic
Coal carbonization products	Petroleum and petroleum products
Coated fabrics	Photographic chemicals
Cosmetics and toilet goods	Pigments and extenders
Drying oils	Plastics
Dye intermediates	Polishes
Electroplating chemicals	Printing inks
Explosive and pyrotechnic materials	Ready mixed paints and enamels
Fertilizers	Rubber and rubber products
Fillers, stoppers and putties	Soaps and other surface active
Footwear	agents
Glass and glassware	Tanning materials and allied
Industrial gases	products
Inks and allied products	Thermal insulation materials
Laboratory glassware, thermometers	Thinners and solvents
and related apparatus	Varnishes and lacquers
Lac and lac products	Water and water treatment
Leather, leather goods and leather	Water based paints
dressings	Unclassified

OTHER PUBLICATIONS

ISI Bulletin (Publishea Every M	onth)			
Single Copy		•••		Rs 3:00
Annual Subscription .			•	Rs 25 ·00
Standards: Monthly Additions				
Single Copy		•••		Re 0⋅30
Annual Subscription	• • •	•••	•••	Rs 3 ∙00
Annual Reports (from 1948-49 C				
Handbook of ISI Publications, 19		•••	•••	
Addendum to 'Handbook of ISI	Publications,	1970 '		Rs 2.50
Annual Reports (from 1948-49 C	nwards) 970 .	•••	•••	Rs 2:00 to 5:00 Rs 12:00 Rs 2:50

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 1

Te lephone: 27 01 31 (20 lines)	Telegrams: Manaksanstha		
Branch Offices:		Telephone	
O-18 New Civil Hospital Annexe, Asarva	Ahmedabad 16	She Short	
F Block, Unity Bidg, Narasimharaja Square	Bangalore 2	2 76 49	
534 Sardar Vallabhbhai Patel Road	Bombay 7	35 69 44	
5 Chowringhee Approach	Calcutta 13	23-08 02	
5-9-201/2-A (First Floor), Chirag Ali Lane	Hyderabad 1	5 34 35	
117/418 B Sarvodaya Nagar 5	Kanpur 5	82 72	
54 General Patters Road	Madras 2	8 72 78	